



Pura Fresh Specifications

	Stage 1	Stage 2	Stage 3	Stage 4
Description	Sediment Filter	Pre-Carbon Filter	RO Membrane	Post-Carbon Filter
Purpose	Sediment Removal	Chlorine Taste & Odor	TDS Reduction	Polishing Taste & Odor
Type	Polypropylene	Carbon Block	Thin Film Composite Membrane	Carbon Block
Micron	5	5	N/A	5
Capacity*	2,000 Gallons	2,000 Gallons	N/A	2,000 Gallons

* May vary depending on water quality

RO Membrane	
Purpose	TDS Reduction
Type	Thin Film Composite Membrane
Recovery	25%
TDS Reduction %	95%
Rating	50 and 75 GPD
Minimum Flow Rate @ 60psi	0.5 gal/min
System Dimensions	14.84" w x 13.46" h x 5.08" d
Quick Change Filter Dimensions	3.15" w x 11.17" h
Inlet/Outlet Connections	1/4" Quick Connect
Working Temperature Range	4-38° C (40-100° F)
Working Pressure Range	207-828 kPa (30-120 psi)

Feed Water Guidelines	
Maximum TDS	2,000 ppm
Hardness	<7gpg
Iron (Fe)	<0.2ppm
Manganese (Mn)	<0.05ppm
Hydrogen Sulfide	0.0ppm
Turbidity	<1.0NTU
Feed Water Pressure	40-100psi
Temperature	40-100° F
pH Range	3.0-11.0

Note: Pretreatment suggested if conditions exceed parameters.
Must be installed on potable water.